

# Euroengel

## Professional mobile refrigeration

T0022 FDN -24°C		<p><b>Top Loader - 22 Lt</b>            -24°C (+30°C T<sub>max</sub>)            12-24Vdc 9-4 A 100-240Vac 1,6-0,8 A 50-60 Hz            65-70 mm PU K&lt; 0,40 Wm<sup>2</sup>K            15 kg</p>		<p><b>Top Loader - 140 Lt</b>            NDN: -10°C (+30°C T<sub>max</sub>)            FDN: -24°C (+30°C T<sub>max</sub>)            12-24Vdc 9-4 A (18-8 A)            100-240Vac 1,6-0,8 A (3-1,5 A) 50-60 Hz            80-100 mm PU K&lt; 0,40 Wm<sup>2</sup>K            32 kg (57 kg)</p>		T0140 NDN -10°C T0140 FDN -24°C
T0032 FDN -24°C		<p><b>Top Loader - 32 Lt</b>            -24°C (+30°C T<sub>max</sub>)            12-24Vdc 9-4 A 100-240Vac 1,6-0,8 A 50-60 Hz            65-70 mm PU K&lt; 0,40 Wm<sup>2</sup>K            17 kg</p>		<p><b>Top Loader - 330 Lt</b>            NDN: +1°C (+30°C T<sub>max</sub>)            FDN: -21°C (+30°C T<sub>max</sub>)            12-24Vdc 9-4 A (18-8 A)            100-240Vac 1,6-0,8 A (3-1,5 A) 50-60 Hz            100 mm PU K&lt; 0,40 Wm<sup>2</sup>K            84 kg (94 kg)</p>		T0330 NDN +1°C T0330 FDN -21°C
T0056 FDN -24°C		<p><b>Top Loader - 56 Lt</b>            -24°C (+30°C T<sub>max</sub>)            12-24Vdc 9-4 A 100-240Vac 1,6-0,8 A 50-60 Hz            70 mm PU K&lt; 0,40 Wm<sup>2</sup>K            19 kg</p>		<p><b>Front opening - 140 Lt</b>            -10°C (+30°C T<sub>max</sub>)            12-24Vdc 9-4 A 100-240Vac 1,6-0,8 A 50-60 Hz            80-100 mm PU K&lt; 0,40 Wm<sup>2</sup>K            32 kg</p>		F0140 NDN -10°C
T0082 FDN -24°C		<p><b>Top Loader - 82 Lt</b>            -24°C (+30°C T<sub>max</sub>)            12-24Vdc 9-4 A 100-240Vac 1,6-0,8 A 50-60 Hz            80 mm PU K&lt; 0,40 Wm<sup>2</sup>K            29 kg</p>		<p><b>Front opening - 330 Lt</b>            +1°C (+30°C T<sub>max</sub>)            12-24Vdc 9-4 A 100-240Vac 1,6-0,8 A 50-60 Hz            100 mm PU K&lt; 0,40 Wm<sup>2</sup>K            80 kg</p>		F0330 NDN +1°C

## The cold chain on the move!

